U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

SECTION I				
EMERGENCY TELEPHONE NO:				
860-564-3321				
P.O. Box 638, One River Street, Moosup, CT 06354				
TRADE NAME AND SYNONYMS:				
KUSHON Sponge - #6120				
FORMULA:				
Neoprene Rubber Base and Lycra Fabric				

	SECT	TON II	- HAZAR	DOUS INGREDIENTS			
PAINTS, PRESERVATIVES & SOLVENTS		%	TLV (Units)	ALLOYS AND METALLIC COATINGS		%	TLV (Units)
PIGMENTS	NA			BASE METAL	NA		
CATALYST	NA			ALLOYS	NA		
VEHICLE	NA			METALLIC COATINGS	NA		
SOLVENTS	NA			FILLER METAL PLUS COATING OR CORE FLUX	NA		
ADDITIVES	NA			OTHERS	NA		
OTHERS	NA						
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS OR GASES				%	TLV (Units)		
NONE							
1. AS GRISWOLD LLC INTERPRETS 29 CFR 1910.1200 THIS							
PRODUCT SHOULD NOT BE CONSIDERED A HAZARDOUS MATERIAL.							
2. THIS PRODUCT NOT SUBJECT TO SARA TITLE III SECTION 313.							

SECTION III – PHYSICAL DATA					
BOILING POINT (°F)	NONE	SPECIFIC GRAVITY (H2O=1)	1.3-1.5		
VAPOR PRESSURE (mm Hg)	NONE	PERCENT, VOLATILE BY VOLUME (%)	NIL		
VAPOR DENSITY (AIR=1)	NONE	EVAPORATION RATE (=1)			
SOLUBILITY IN WATER	NONE				
APPEARANCE AND ODOR	SOLID-NIL		·		

SECTION IV – FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT (Method Used)	FLAMMABLE LIMITS	Lel	Uel			
IGNITION TEMP. 750°F						
EXTINGUISHING MEDIA		•				
ANY						
SPECIAL FIRE FIGHTING PROCEDURES						
NORMAL SMOKE PROTECTION						
UNUSUAL FIRE AND EXPLOSION HAZARDS						
NONE						

	SECTION	V – HEA	LTH HAZARD DA	ATA	
THRESHOLD LIMIT VALUE	NONE				
EFFECTS OF OVEREXPOSU					
	NONE				
EMERGENCY AND FIRST AID	O PROCEDURES				
	SECTIO	N VI – R	EACTIVITY DATA	A	
STABILITY	UNSTABLE		CONDITIONS TO AV		
	STABLE	Х		NONE KNO	WN
INCOMPATABILITY (Materials	•				
HAZARDOUS DECOMPOSITION	NONE KNOWN				
HAZARDOUS DECOMPOSITI		USTION	PRODUCTS CON	ISIDER TOXIC	
HAZARDOUS	MAY OCCUR		CONDITIONS TO AV		
POLYMERIZATION	WILL NOT OCCUR	X		NONE KNO	WN
		_1			
_	SECTION VIII	CDILL C	R LEAK PROCE	DUDEC	
STEPS TO BE TAKEN IN CAS			JR LEAK PROCE	DUKES	
OTEL O TO BE TAILEN IN CAC	DE MATERIAL IS RELEASED (JK SI ILLED			
WASTE DISPOSAL METHOD					
	PRODUCT AS DI				
	CLASSIFIED AS			STE PER	
	CFR VOL. 45/NO	<u>. 98 PAR</u>	T 261		
	SECTION VIII – S	3PECIAL	PROTECTION IN	NFORMATION	NONE
RESPIRATORY PROTECTION VENTILATION		XHAUST		SPECIAL	
VENTIENTION					
PROTECTIVE GLOVES	MECHAN	IICAL (GENEF	RAL) EYE PROTECTION	OTHER	
OTHER PROTECTIVE EQUIP	MENT		LILFROILCION		
	SECTION I	X - SPE	CIAL PRECAUTION	ONS	
PRECAUTIONS TO BE TAKE!					
	NONE				
OTHER PRECAUTIONS					
		SEC	TION X		
SIGNATURE			DATE		
John J. Tieky , Jr.	fr. 10/01/2015				
TITLE			•		
Technical Director					

NOTE: Information of a technical nature is based on laboratory tests which either GRISWOLD LLC conducts or sends to an independent laboratory for testing for determination of uses as requested in writing by customer. GRISWOLD LLC believes these to be reliable. However, GRISWOLD LLC has no control over the application of the material to, or part of, the final **product** and **therefore**, GRISWOLD LLC makes **no express or implied warranty of result, fitness or merchantability.** The customer should determine reliability for the end use or particular application.

