

**KUSHON<sup>®</sup> Sponge**  
**&**  
**enlighten-u<sup>®</sup> Microcellular Polyurethane**  
**Automotive Product Guide**

Product Family	Product	Hardness (cfd in psi)	Typical Applications
enlighten- <u>u</u> <sup>®</sup> Microcellular Urethane	<b>U7S15</b>	Super Soft (1 - 5)	BSR/NVH, Sealing and Cushioning
	<b>U7E17</b>	Soft (4 - 8)	
	<b>U7E21</b>	Medium (7 - 13)	
	<b>U7E26</b>	Firm (12 - 18)	
	<b>U7H15</b>	Extra Firm (20 - 50)	
	<b>U7H20</b>	Ultra Firm (40 - 80)	
	<b>U7H25</b>	Ultra Firm (60 - 130)	
<b>KUSHON<sup>®</sup></b> Cellular Sponge	<b>3110</b>	Soft (2 - 5)	Non-skid Bin Liners
	<b>3120</b>	Medium (5 - 10)	
	<b>3130</b>	Medium Firm (10 - 16)	
	<b>3140</b>	Firm (16 - 22)	
	<b>3150</b>	Extra Firm ( > 22)	

Determining the suitability for use of a material in any given application is the responsibility of the customer.

**NOTE:** Information of a technical nature is based on laboratory tests which either GRISWOLD LLC conducts or sends to an independent laboratory for testing for determination of uses as requested in writing by customer. GRISWOLD LLC believes these to be reliable. However, GRISWOLD LLC has no control over the application of the material to, or part of, the final **product** and **therefore**, GRISWOLD LLC makes **no express or implied warranty of result, fitness or merchantability**. The customer should determine reliability for the end use or particular application.